

# American DJ®

## MEGA FLASH DMX



## User Instructions

American DJ®  
4295 Charter Street  
Los Angeles Ca. 90058  
www.americandj.com

### Mega Flash DMX™

### Introduction

**Unpacking:** Thank you for purchasing the Mega Flash DMX™ by American DJ®. Every Mega Flash DMX™ has been thoroughly tested and has been shipped in perfect operating condition. Carefully check the shipping carton for damage that may have occurred during shipping. If the carton appears to be damaged, carefully inspect your unit for damage and be sure all accessories necessary to operate the unit have arrived intact. In the event damage has been found or parts are missing, please contact our customer support number for further instructions. Please do not return this unit to your dealer without first contacting customer support at the number listed below.

**Introduction:** To optimize the performance of this product, please read these operating instructions carefully to familiarize yourself with the basic operations of this unit. The Mega Flash DMX™ is a 800 watt strobe, that has a flash rate range of 1 to 15 flashes per second. Up to 16 units may be linked together and controlled by single controller. The units' intensity, and flash rate can be manually adjusted using the dipswitches.

**Customer Support:** American DJ® provides a toll free customer support line, to provide set up help and to answer any question should you encounter problems during your set up or initial operation. You may also visit us on the web at [www.americandj.com](http://www.americandj.com) for any comments or suggestions. For service related issue please contact American DJ®. Service Hours are Monday through Friday 9:00 a.m. to 5:00 p.m. Pacific Standard Time.

Voice: (800) 322-6337

Fax: (323) 582-2610

E-mail: [support@americandj.com](mailto:support@americandj.com)

To purchase parts online visit <http://parts.americandj.com>

**Warning!** To prevent or reduce the risk of electrical shock or fire, do not expose this unit to rain or moisture.

**Caution!** There are no user serviceable parts inside this unit. Do not attempt any repairs yourself, doing so will void your manufactures warranty.

*Please recycle the shipping carton when ever possible.*

## Mega Flash DMX™

## Features

- Bright 800 Watt Lamp ZB-800
- Adjustable Flash Rate, and Intensity Rate
- Flash Rate range of 1 to 15 Flashes per Second
- Thermostat Protection
- Large coverage area
- Easy lamp Replacement
- Built-In Adjustable Hanging Yoke

## Mega Flash DMX™

## Warranty Registration

The Mega Flash DMX™ carries a one year (365 days) limited warranty. Please fill out the enclosed warranty card to validate your purchase. All returned service items whether under warranty or not, must be freight pre-paid and accompany a return authorization (R.A.) number. The R.A. number must be clearly written on the outside of the return package. A brief description of the problem as well as the R.A. number must also be written down on a piece of paper and included in the shipping container. If the unit is under warranty, you must provide a copy of your proof of purchase invoice. You may obtain a R.A. number by contacting customer support at (800) 322-6337.

## Mega Flash DMX™

## Cleaning Instructions

Due to fog residue, smoke, and dust cleaning the fixture should be carried out periodically to optimize light output.

1. Use normal glass cleaner and a soft cloth to wipe down the outside casing every 20 days.
2. Use normal glass cleaner with a soft cloth to wipe down the inside reflector and lens every 30-60 days.
3. Always be sure to dry all parts completely before plugging the unit back in.
4. Frequent cleaning the unit will extend lamp life and ensure the fixtures reliability.

Cleaning frequency depends on the environment in which the fixture operates (i.e. smoke, fog residue, dust, dew). In heavy use we recommend cleaning on a monthly basis. Periodic cleaning will ensure longevity, and crisp beam output.

## Mega Flash DMX™

## Safety Warnings

**Safety Issues:** This unit may blow a fuse if the maximum allotted load of 15 amps is reached. If the fuse needs replacement, always replace the fuse with same exact type that was removed, unless otherwise instructed by an authorized American DJ® service technician. Use of a different type fuse from that which is recommended may cause fire or electric shock and will void the manufacturer's warranty.

- To reduce the risk of electrical shock or fire, do not expose this unit to rain or moisture.
- Do not spill water or other liquids into or on to your unit.
- Do not attempt to remove or break off the ground prong from the electrical cord. This prong is used to reduce the risk of electrical shock and fire in case of an internal short. Do not attempt to operate this unit if the power cord has been frayed or broken.
- Disconnect from main power before making any type of connection.
- Do not remove the cover under any conditions. There are no user serviceable parts inside.
- Always be sure to mount this unit in an area that will allow proper ventilation. Allow about 6" (15cm) between this device and a wall.
- Do not attempt to operate this unit, if it becomes damaged.
- This unit is intended for indoor use only, use of this product outdoors voids all warranties.
- During long periods of non-use, disconnect the unit's main power.
- Always mount this unit in safe and stable matter.
- Power cords should be routed so they are not likely to be walked on, pinched by items placed upon or against them.
- Cleaning -The fixture should be cleaned only as recommended by the manufacturer. See page 6 for cleaning details.
- Heat -The appliance should be situated away from heat sources such as radiators, heat registers, stoves, or other appliances (including amplifiers) that produce heat.
- The fixture should be serviced by qualified service personnel when:
  - A. The power-supply cord or the plug has been damaged.
  - B. Objects have fallen, or liquid has been spilled into the unit.
  - C. The unit has been exposed to rain or water.
  - D. The unit does not appear to operate normally or exhibits a marked change in performance.

**Power Supply:** Before plugging your unit in, be sure the source voltage in your area matches the required voltage for your American DJ® Mega Flash DMX.™ The American DJ® Mega Flash DMX™ is 120v only. Because line voltage may vary from venue to venue, you should be sure your unit voltages matches the wall outlet voltage before attempting to operate your fixture.

**DMX-512:** DMX is short for Digital Multiplex. This is a universal protocol used as a form of communication between intelligent fixtures and controllers. A DMX controller sends DMX data instructions from the controller to the fixture. DMX data is sent as serial data that travels from fixture to fixture via the DATA “IN” and DATA “OUT” XLR terminals located on all DMX fixtures (most controllers only have a DATA “OUT” terminal).

**DMX Linking:** DMX is a language allowing all makes and models of different manufactures to be linked together and operate from a single controller, as long as all fixtures and the controller are DMX compliant. *To ensure proper DMX data transmission, when using several DMX fixtures try to use the shortest cable path possible. The order in which fixtures are connected in a DMX line does not influence the DMX addressing. For example; a fixture assigned a DMX address of 1 may be placed anywhere in a DMX line, at the beginning, at the end, or anywhere in the middle. When a fixture is assigned a DMX address of 1, the DMX controller knows to send DATA assigned to address 1 to that unit, no matter where it is located in the DMX chain.*

**Dipswitches in DMX mode:** This unit uses dipswitches to assign a DMX address. Each dipswitch represents a binary value.

Dipswitch 1 address equals 1  
 Dipswitch 2 address equals 2  
 Dipswitch 3 address equals 4  
 Dipswitch 4 address equals 8  
 Dipswitch 5 address equals 16  
 Dipswitch 6 address equals 32  
 Dipswitch 7 address equals 64  
 Dipswitch 8 address equals 128  
 Dipswitch 9 address equals 256

*Dipswitch 10 - Some units omit dipswitch 10. When a unit does include dipswitch #10, it is usually used for special functions such as*

*sound activation.*

**Assigning DMX Address:** Each dipswitch has a preset value. A specific DMX address is set by combining the dipswitches that sum your desired value. For example: To achieve a DMX address of 7, combine dipswitches 1, 2, and 3. Since dipswitch 1 has a value of 1, dipswitch 2 has a value of 2, and dipswitch 3 has a value of 4, the combination of the three create a DMX value of 7. (See example below).

Set DMX address 1:	Set DMX address 7:		
Dip-switches #	1 = 1	Dip-switches #	1 = 1
			2 = 2
			3 = 4
			= 7

**Data Cable (DMX Cable) Requirements (For DMX and Master/Slave Operation):** The Mega Flash DMX™ can be controlled via DMX-512 protocol. The Mega Flash DMX™ is a two channel DMX unit. The DMX address is set on the side panel of the Mega Flash DMX™ Your unit and your DMX controller require a standard 3-pin XLR connector for data input and data output (Figure 1). If you are making your own cables, be sure to use standard two conductor shielded cable (This cable may be purchased at almost all pro sound and lighting stores). Your cables should be made with a male and female XLR connector on either end of the cable. Also remember that DMX cable must be daisy chained and can not be split.



Figure 1

**Notice:** Be sure to follow figures two and three when making your own cables. Do not use the ground lug on the XLR connector. Do not connect the cable's shield conductor to the ground lug or allow the shield conductor to come in contact with the XLR's outer casing. Grounding the shield could cause a short circuit and erratic behavior.




Figure 2



Figure 3

XLR Pin Configuration
Pin 1 = Ground
Pin 2 = Data Compliment (negative)
Pin 3 = Data True (positive)

**Special Note: Line Termination.** When longer runs of cable are used, you may need to use a terminator on the last unit to avoid erratic behavior. A terminator is a 90-120 ohm 1/4 watt resistor which is connected between pins 2 and 3 of a male XLR connector (DATA + and DATA -). This unit is inserted in the female XLR socket of the last unit in your daisy chain to terminate the line. Using a cable terminator (ADJ part number Z-DMX/T) will decrease the possibilities of erratic behavior.



Termination reduces signal errors and avoids signal transmission problems and interference. It is always advisable to connect a DMX terminal, (Resistance 120 Ohm 1/4 W) between PIN 2 (DMX-) and PIN 3 (DMX +) of the last fixture.

Figure 4

**5-Pin XLR DMX Connectors.** Some manufactures use 5-pin XLR connectors for DATA transmission in place of 3-pin. 5-pin XLR fixtures may be implemented in a 3-pin XLR DMX line. When inserting standard 5-pin XLR connectors in to a 3-pin line a cable adaptor must be used, these adaptors are readily available at most electric stores. The chart below details a proper cable conversion.

3-Pin XLR to 5-Pin XLR Conversion		
Conductor	3-Pin XLR Female (Out)	5-Pin XLR Male (In)
Ground/Shield	Pin 1	Pin 1
Data Compliment (- signal)	Pin 2	Pin 2
Data True (+ signal)	Pin 3	Pin 3
Not Used		Pin 4 - Do Not Use
Not Used		Pin 5 - Do Not Use

**Power Supply:** This unit is available only in 120v. Before plugging your unit in be sure the source voltage in your area matches the required voltage for your American DJ® Mega Flash DMX.™

**General Operation:** This fixture is designed to operate as a stand alone, sound-active unit, or in a Master/Slave configuration. It can also operate via DMX controller. The Mega Flash DMX™ is ready to be plugged in out of the box.

**Duty Cycle:**

Because the Mega Flash DMX™ can be used for continuous output (ie while simulating lightning), it can build up intense heat. Due to the build up of intense heat the unit should not run for 15 minutes continuously. After 15 minutes of continuous use, allow the unit to cool for about fifteen minutes, this will greatly increase the lamp life and insure product longevity.

**Operating Modes:**

**Stand Alone and Sound Active Modes:**

To run the strobe in stand alone mode, dipswitches #9 and #10 must be in the “off” position. In stand alone mode the unit will function as a normal strobe light. Rate (speed), and intensity (brightness), are set directly on the unit. Note that these settings are made using the knobs on the back of the unit. Once the settings are made they can only be changed by physically adjusting the knobs on the unit. Be aware of this if you plan on installing your strobe in a permanent application, if your are not satisfied with your settings you will have to physically remove the unit and adjust the knobs.

In sound active mode, dipswitch #9 must be in the “on” postion. The dimming will still be controlled by the knob on the back of the unit. But the beat of the music will control the flash speed. Note that these settings are made using the knobs on the back of the unit. Once the settings are made they can only be changed by physically adjusting the knobs on the unit. Be aware of this if you plan on installing your strobe in a permanent application, if your are not satisfied with your settings you will have to physically remove the unit and adjust the knobs.

**Universal DMX Control:** This mode allows you to use a universal DMX-512 controller such as the American DJ® DMX Operator™ or

Show Designer.™

1. To control your fixture in DMX mode, follow the set-up procedures on pages 5-6 as well as the set-up procedures included with your DMX controller.
2. For longer cable runs (more than a 100 feet) use a terminator on the last fixture.
3. Assign your desired address to the unit, and “flip” dipswitch #10 to the “on” position.
4. The Mega Flash DMX™ uses two DMX channels. Channel 1 controls the flash speed and channel 2 controls the dimmer. Use your DMX controller to activate the various built-in patterns. See the bottom of this page for the DMX traits.
5. For help operating in DMX mode consult the manual included with your DMX controller.

**NOTE:** If running in Master/Slave address configuration while using a DMX controller, follow the DMX address chart on page 12.


## Mega Flash DMX™

## DMX Traits

Channel	Value	Function
1	0 - 255	FLASH SPEED
2	0 - 255	FLASH DIMMING

## Mega Flash DMX™

## Fuse and Lamp Replacement



**Halogen Lamp Warning!** This fixture is fitted with halogen lamps which are highly susceptible to damage if improperly handled. Never touch the lamps with your bare fingers as the oil from your hands will shorten lamp life. Also, never move the fixture until the lamps have had ample time to cool. Remember, lamps are not covered under warranty conditions.

**Caution:** Always replace with the exact same type lamp and fuse, unless otherwise specified by an authorized American DJ® technician. Replace with anything other than the specified part can damage your unit and will void your manufacturer's warranty.

**Warning! Allow the lamp to discharge all current. Allow the unit 24hrs. to discharge before changing the lamp. Stored current can cause a very severe shock.**

**Warning:** If after you have replaced the lamp or fuse and you continue to blow either one, STOP using the unit. Contact customer support for further instructions, you may have to return the unit for servicing. Continuing to use the unit may cause serious damage.

**Fuse Replacement:** Disconnect the unit's main power supply. Insert a standard flat head screw driver in to the fuse holder housing (located on the rear of the unit). Turn the screwdriver in a counter-clockwise direction to remove the fuse holder. Remove the old fuse and discard it, replace the fuse with the same type. Insert the fuse holder back into its housing and turn in a clockwise direction to secure the holder in place.

**Lamp Replacement:** Caution! Never open the unit when in use. Always disconnect the main power and allow the fixture ample time to cool before attempting to replace the lamp. Lamp replacement has been made simple by incorporating a remove tray that is retained by a single thumb screws. Again, please remember to always replace with the exact same type lamp.

1. Be sure to follow the proper procedures when handling halogen lamps. Never touch the new lamp with your bare fingers.
2. Unscrew and remove the four phillips screws located on the front cover of the unit.
3. Located on each side of the lamp are white ceramic wire connection blocks.
4. The ceramic block on the left side has one lamp wire connected to the bottom of it, they are secured by one phillips screw each. On the right side there are two lamp wires connected to the bottom of the ceramic block.
5. **NOTICE:** When you disconnect the lamp wires to replace the lamp, you will have to remember which wire went where. They must be connected the same.
6. Push out the metal tabs on each side of the lamp, and pull out the lamp as you do this. Replace the lamp with an exact match. Connect the three wires to the ceramic blocks as they were when you disconnected them. Reassemble in reverse order.

**1-YEAR LIMITED WARRANTY**

A. American DJ® hereby warrants, to the original purchaser, American DJ® products to be free of manufacturing defects in material and workmanship for a period of one year (365 days) from the date of purchase. This warranty shall be valid only if the product is purchased within the United States of America, including possessions and territories. It is the owner's responsibility to establish the date and place of purchase by acceptable evidence, at the time service is sought.

B. For warranty service, send the product only to the American DJ® factory. All shipping charges must be pre-paid. If the requested repairs or service (including parts replacement) are within the terms of this warranty, American DJ® will pay return shipping charges only to a designated point within the United States. If the entire instrument is sent, it must be shipped in its original package. No accessories should be shipped with the product. If any accessories are shipped with the product, American DJ® shall have no liability whatsoever for loss of or damage to any such accessories, nor for the safe return thereof.

C. This warranty is void if the serial number has been altered or removed; if the product is modified in any manner which American DJ® concludes, after inspection, affects the reliability of the product; if the product has been repaired or serviced by anyone other than the American DJ® factory unless prior written authorization was issued to purchaser by American DJ®; if the product is damaged because not properly maintained as set forth in the instruction manual.

D. This is not a service contract, and this warranty does not include maintenance, cleaning or periodic check-up. During the period specified above, American DJ® will replace defective parts at its expense, and will absorb all expenses for warranty service and repair labor by reason of defects in material or workmanship. The sole responsibility of American DJ® under this warranty shall be limited to the repair of the product, or replacement thereof, including parts, at the sole discretion of American DJ®. All products covered by this warranty were manufactured after January 1, 1990, and bear identifying marks to that effect.

E. American DJ® reserves the right to make changes in design and/or improvements upon its products without any obligation to include these changes in any products theretofore manufactured.

F. No warranty, whether expressed or implied, is given or made with respect to any accessory supplied with products described above. Except to the extent prohibited by applicable law, all implied warranties made by American DJ® in connection with this product, including warranties of merchantability or fitness, are limited in duration to the warranty period set forth above. And no warranties, whether expressed or implied, including warranties of merchantability or fitness, shall apply to this product after said period has expired. The consumer's and or Dealer's sole remedy shall be such repair or replacement as is expressly provided above; and under no circumstances shall American DJ® be liable for any loss or damage, direct or consequential, arising out of the use of, or inability to use, this product.

G. This warranty is the only written warranty applicable to American DJ® Products and supersedes all prior warranties and written descriptions of warranty terms and conditions heretofore published.

**Model: Mega Flash DMX™**

<b>Voltage*:</b>	120v~60Hz
<b>Lamp:</b>	ZB-800 800w Strobe lamp
<b>Fuse:</b>	15A 250v
<b>Dimensions:</b>	15.9" (L) x 5.3" (W) x 4.1" (H)
<b>Weight:</b>	4.8 Lbs./ 2.2 Kgs.
<b>Duty Cycle:</b>	15 minutes on/off
<b>Ventilation:</b>	Air Cooled
<b>Warranty:</b>	1 Year (365 Days)

*\*Voltage is preset at the factory and can not be changed by the user.*

**Please Note:** Specifications and improvements in the design of this unit and this manual are subject to change without any prior written notice.

©American DJ Supply

American DJ World Headquarters:

4295 Charter Street Los Angeles, CA 90058 USA

Tel: 323-582-2650 / Fax: 323-582-2610

Web: [www.americandj.com](http://www.americandj.com) / E-mail: [info@americandj.com](mailto:info@americandj.com)